


STT293 18t/16t/12t



附著道數 Number of tie collars =(H-A-C)/B+1
超過100m高度，需降低載荷，請與公司聯繫。 Load should be reduced when the height exceeds 100m. Please contact Yongmao for details.


主要性能參數 Specifications

機構 Mechanism								電動機 Motor kW
			m/min	t	m/min	t		
	18t	75LFV45A☆	0—38 0—46 0—76	9.0 6.0 3.0	0—19 0—23 0—38	18.0 12.0 6.0	680m	75
		75LFV45DBA	0—40 0—96 0—160	9.0 3.0 1.0	0—20 0—48 0—80	18.0 6.0 2.0	1030m >1030m *	75
	16t	75LFV40	0—47 0—57 0—95	8.0 6.0 3.0	0—24 0—28 0—47	16.0 12.0 6.0	550m >550m *	75
	12t	55LFV30 ☆	0—44 0—53 0—88	6.0 4.0 1.7	0—22 0—27 0—44	12.0 8.0 3.5	630m	55
		75LFV30	0—60 0—80 0—120	6.0 3.0 1.5	0—30 0—40 0—60	12.0 6.0 3.0	1030m >1030m *	75
	7.5DFV08		0—69 m/min					7.5
	RTC290 ☆		0—0.8 rpm					2x145 N·m
	7.5RFCV		0—0.8 rpm					2x7.5 (2x145 N·m)
	RT		12.5—25.0 m/min					4x2.6/5.2
 電壓 Pressure			kVA					
380V (± 10%) 50 Hz			75LFV45A, 75LFV40, 75LFV30: 125 55LFV30 : 100 75LFV45DBA : 145					

EN 14439 FEM 1005 C/25 * 與製造商聯繫 Contact us, please.
★ 標準配置 Standard configuration.
本技術參數不受法律約束，技術資訊請詳見相應說明書。
Specifications and data are not legally binding. For any technical information, please refer to corresponding instructions.


永茂建机 YONGMAO

STT293 18t/16t/12t



載荷表 Load Chart

18t 雙小車 2-trolley L-18-A(B)-1-V1.0												
R (m)	倍率 Fall	R(C _{max}) (m)	C _{max} (t)	30	34	40	44	50	54	60	64	74
74	👁	14.3	18.00	7.02	6.45	5.05	4.48	3.80	3.43	2.98	2.72	2.39
	👁	25.9	9.00	7.66	6.65	5.55	4.98	4.30	3.93	3.48	3.22	2.89
70	👁	14.6	18.00	7.42	6.64	5.25	4.66	3.96	3.58	3.11	2.84	2.50
	👁	26.7	9.00	7.92	6.88	5.75	5.16	4.46	4.08	3.61	3.34	3.00
64	👁	15.7	18.00	8.30	7.28	5.83	5.19	4.42	4.01	3.49	3.20	
	👁	29.1	9.00	8.80	7.58	6.33	5.69	4.92	4.51	3.99	3.70	
60	👁	15.7	18.00	8.30	7.28	5.84	5.20	4.43	4.02	3.50		
	👁	29.1	9.00	8.80	7.58	6.34	5.70	4.93	4.52	4.00		
54	👁	15.7	18.00	8.40	7.33	5.95	5.30	4.52	4.10			
	👁	29.6	9.00	8.90	7.72	6.45	5.80	5.02	4.60			
50	👁	16.3	18.00	8.60	7.70	6.30	5.62	4.80				
	👁	31.0	9.00	9.00	8.13	6.80	6.12	5.30				
44	👁	18.2	18.00	10.10	8.82	7.28	6.50					
	👁	35.0	9.00	9.00	8.00	7.78	7.00					
40	👁	18.5	18.00	10.35	9.05	7.50						
	👁	35.9	9.00	9.00	8.00							
34	👁	17.16	18.00	9.93	8.70							
	👁	34.0	9.00	9.00								
30	👁	18.5	18.00	10.35								
	👁	30.0	9.00	9.00								



EN 14439 FEM 1005 C/25

平头系列 Topless

V 5.0-03132020

辽宁省抚顺市顺城区前岭永茂工业园 113126 YONGMAO Industrial Park ,Shuncheng, Fushun Liaoning,China.
Tel: 024-57648899 Fax: 024-57649999 Email: sun@yongmao.com.cn web: www.yongmao.com.cn

平头系列 Topless
V 5.0-03132020

office@sky-line.co.il ,03-9033901 טלי
www.sky-line.co.il ,44820 מ.ת ברקן 143



המנוף שלך להצלחה



YONGMAO HOLDINGS LIMITED



המנוף שלך להצלחה

